## **Scope of Services**

Description: The following specification covers the requirements for a 64,000 lb. GVWR, 4 x 6, Tandem Axle 12-yard Dump Truck. Acceptable chassis are limited to Freightliner M2–112 or International Workstar.

			Complies with Requirements
1.0		I (Weight, Dimensions, Cab, Capacities) Chassis Make	Make:
	1.2	Chassis Model	Model:
	1.4 1.5 1.6 1.7 1.8 1.9 1.10 1.11 1.12 1.13 1.14 1.15 1.16 1.17 1.18	Conventional Cab / Set Back Axle (List CA) 64,000 lb. GVW – 187" Wheelbase Single Front Axle – 18,000 lb. Tapered Leaf Front Suspension Front Wheels: Steel 10 Hole Hub Piloted Front Tires: 385 Front Float Tandem Rear Axle – 46,000 lb. Hendrickson RT 463 Rear Suspension Rear Wheels: Steel 10 Hole Hub Piloted Rear Tires: 11R22.5 Goodyear G124 or approved equivalent Power Divider with Warning Light & Buzzer C – Channel Inner Frame Reinforcement Paint – Overall White / Neutral Interior Radio, Heat, and Air Conditioning Drivers Air Ride Suspension Seat Cab-Welded Steel Galvanized or Aluminum Shell with rust preventative coating Frame: Steel Construction matched to GVW and Mounted Body of Truck Front Bumper: Painted Steel Air Dryer: Bendix AD9 Heated (or approved equivalent) Floor Covering: Black Rubber Mats Steering Wheel: 18" Two Spoke	CA Length:
2.0	Engine	e – <b>Powertrain</b> Engine Make	Make:
	2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 2.10	Engine Model Diesel Engine 2010/2011 EPA / CARB Compliant Horsepower (gross): 350 HP 6 Cylinder Diesel, 11L minimum Torque Minimum 850 lb/ft Fuller 14210B 10 speed Manual with overdrive (or approved equivalent) Alternator: 12 Volt 100 Amp Injection Pump, Electrical Engine Control Air Restriction Monitor, Intake Mounted Fuel Capacity: 70 gallon minimum	Model:  Y N Y N Y N Y N Y N Y N Y N Y N Y N Y N Y N Gapacity:gal
3.0	Dump 3.1 3.2 3.3 3.4 3.5 3.6	Body Godwin (or approved equivalent) 12 yard Dump with provisions for sideboards Hydraulic Hoist 45 Degree Dump Angle Top Hinged Tailgate Underside Body Undercoated Painted Black Electric Tarp System	Y N Y N Y N Y N Y N Y N
4.0	Body 4.1 4.2 4.3 4.4 4.5 4.6 4.7	and Chassis Accessories Pintle Hitch 30,000 lbs. T-125 Two Safety Chain D Rings Wheel Chocks with Underbody Holders Back Up Alarm Mud Flaps – Solid Color / No Advertising One 5 lb. Fire Extinguisher Triangular Reflector Kit in Cab	Y N Y N Y N Y N Y N Y N Y N

5.0	<b>Safety</b> 5.1 5.2 5.3 5.4 5.5 5.6 5.7 5.8 5.9 5.10 5.11	Standard Strobe Lights with Guard Dual Tone Back Up Alarm Six (6) – Way Trailer Receptacle Horn: Single Air Trumpet Mirrors: West-Coast to include 7.5" Convex Mounted to Lower Mirror Bracket Windshield Wipers: 2 speed with intermittent Brakes: Automatic Slack Adjusters Front & Rear Daytime Running Lights Circuit Protection: Fuses except Headlamp & Wiper Circuits (which use circuit breakers) Hand Throttle: Electronic Hand Throttle operated through cruise control when in PTO mode only Engine Protection: Engine Shut Down System monitoring high water temperature, low oil pressure, or high exhaust temperature	Y
6.0	<b>Final I</b> 6.1	<b>Delivery</b> Delivery of Complete Unit – FOB Fleet Garage	Y N Days:
7.0	7.1 7.2 7.3 7.4 7.5 7.6	Provide Complete Literature and Specifications Provide User Training Provide two (2) complete Parts/Service Manuals Provide two (2) complete Operator's Manuals Provide two (2) complete Sets of Keys State Terms / Conditions of Warranty	Y N Y N Y N Y N Terms:
	7.7	State Period of Warranty	Period: